

EV355227784

IN THE UNITED STATES PATENT AND TRADEMARK OFFICE

APPLICATION FOR LETTERS PATENT

Adding Recording Functionality to a Media Player

Inventors:

Mehul Y. Shah
Vladimir Rovinsky
Dongmei Zhang

ATTORNEY'S DOCKET NO. MS1-1539US

TECHNICAL FIELD

This disclosure relates to recording multimedia content and specifically to systems and methods to record streaming multimedia content from a source to a computer.

BACKGROUND

Presentations such as movies, commercials, song albums, music concerts, and news broadcast may be represented by multimedia content. Multimedia content may be separated into audio and video content. It is becoming more commonplace for computers such as personal computers (PC) to render (i.e., play) multimedia content. A PC may access such multimedia content from a local source such as a resident storage device (e.g. the PC's hard disk) and/or resident media device (e.g., DVD or CD drive on the PC). In particular cases, the PC may access multimedia content from other sources such as other computers and/or media devices through a network connection.

Accessing and playing multimedia content may be performed through a "media player" resident in the PC. A media player typically is implemented in software. An example of a media player is Windows® media player (WMP) by the Microsoft® Corporation.

With the use of the Internet, website sources are also able to stream multimedia content to connected PCs. Streamed multimedia content involves transmitting multimedia content from a server (i.e., a website server computer) across a network (i.e. the Internet) in a continuous flow. A PC, and in particular the media player of the PC, may render the multimedia content immediately

1 instead of waiting for an entire file of the multimedia content to be downloaded
2 from the source.

3 Streaming multimedia content from the Internet includes live broadcasts of
4 news events, audio/video programs such as music concerts, and promotional
5 content such as commercials and movie trailers. Streaming multimedia content
6 may defined as “on-demand” and “broadcast” content. For on-demand content, a
7 PC through a media player controls playback experience; for example, when to
8 start playback, when to pause, when to stop playback, and when to seek to a
9 specific position in the content. For “broadcast” content, a website source, in
10 particular a server from which multimedia content originates controls the playback
11 experience; for example, when streaming starts and when streaming ends.

12 PC users may have a limited duration of time to access streaming
13 multimedia content from a website. A live broadcast from a website may only be
14 available for viewing over a defined time. A movie trailer may be removed from a
15 website after the movie is no longer being shown in theatres. Commercials may
16 become outdated and removed from a website.

17 In certain cases, a PC user may desire to record streaming multimedia
18 content for later viewing such as when a user is not available to view a live news
19 broadcast, or desires to record a movie trailer for later reference. In many
20 instances a website providing streaming multimedia content desires that PCs have
21 the ability to record streaming multimedia content. For example, a website
22 operator has goals for promotional material to be viewed often and by a large
23 number of people. Allowing PCs to record the promotional material helps to
24 achieve the website operator’s goals.

1 Although a great deal of multimedia content may be recorded, a significant
2 amount of multimedia content may be copyrighted and should be protected from
3 being recorded. Although a source (i.e., website) may allow a PC user to
4 experience (i.e., render) the multimedia content, the source may desire to protect
5 multimedia content that is copyrighted from being recorded. For example, an
6 Internet "radio station" website broadcasts a new song promoting an artist;
7 however, the artist does not want a PC to be able record the song, but to have
8 people purchase the song by buying an album or paying for rights to record the
9 song.

10 In certain cases, a media player may be embedded in a webpage of a
11 website. An example is that of an Internet "radio station" website. The embedded
12 media player provides a user interface (UI) to a "visitor" of the website; however
13 the UI typically provides limited functionality to the visitor and does not allow the
14 visitor to record multimedia content.

15 Some media players, whether included in a PC or embedded in a webpage,
16 in order to prevent copyrighted content from being copied, forego providing PCs
17 an ability to record multimedia content, whether the multimedia content is
18 copyrighted or not. Therefore a PC user desiring to record non-copyrighted
19 multimedia content for later viewing is not able to perform recording through the
20 media player. This compromises the viewing experience of PC users to view
21 multimedia content when they so desire.

22 23 **SUMMARY**

24 The system and methods described herein include selectively providing a
25 recording component in a media player to allow for recording of protected and

1 non-protected multimedia content, where the recording component may be added
2 to a linked set of components that are used to render the multimedia content.

3 In certain embodiments, the recording component is added to the linked set
4 of components when it is registered and identified to be able to record multimedia
5 content received from particular sources.

6 7 **BRIEF DESCRIPTION OF THE DRAWINGS**

8 Fig. 1 is a block diagram illustrating a system of multiple websites
9 providing multimedia content to a personal computer that is configured to play
10 record the multimedia content using a media player.

11 Fig. 2 is a block diagram illustrating a media player of a personal computer
12 that is configured to receive, render and record multimedia content.

13 Fig. 3 is a block diagram illustrating a stream recorder and programming
14 interfaces for playing and recording multimedia content on a personal computer.

15 Fig. 4 is a flowchart illustrating operation of an exemplary recording
16 session of a personal computer receiving multimedia content.

17 Fig. 5 is a block diagram illustrating a general example of a computer that
18 is used in accordance with the subject matter.

19 20 **DETAILED DESCRIPTION**

21 Fig. 1 shows a system 100 that provides multimedia content to a personal
22 computer configured to play and record the multimedia content.

23 A personal computer (PC) 105 includes an application media player 110
24 that may be implemented in software. Media player 110 is configured to interact
25 with input output devices, processing devices, and other software/hardware

1 devices of PC 105, and is used to render (i.e., play) multimedia content that is
2 received. PC 105 may be considered a playback computer that is capable of
3 rendering multimedia content.

4 Media player 110 includes various software components, and specifically
5 includes a stream recorder component 115. Stream recorder component 115
6 allows non-copyrighted multimedia content that is received and rendered by media
7 player 110 to be recorded. Stream recorder component 115 may be added as a
8 “plug-in” component to media player 110 as further discussed below. As a plug-in
9 component to media player 110, stream recorder 115 and its subcomponents are
10 able to query media player 110 as to states regarding the playing of multimedia
11 content.

12 PC 105 is connected to a network 120 which potentially includes the public
13 Internet. Network 120 is further connected to multiple websites 125(1), 125(2)...
14 125(N). Websites 125 include Internet radio stations, news services, and
15 promotional commercial sites. Multimedia content is streamed from websites 125
16 through network 120 to PC 105. The multimedia content includes audio and video
17 content. Multimedia content which is non-copyrighted or non-protected may be
18 recorded. If authorized to record, PC 105 may record copyrighted or protected
19 multimedia content. However without authorization, multimedia content that is
20 identified as copyrighted (i.e. protected) may not be recorded. Copyrighted
21 multimedia content may employ digital rights management (DRM) techniques for
22 protection, where DRM techniques make use of encryption keys to encrypt and
23 decrypt protected content. Authorization allowing PC 105 to record may be
24 through a DRM protocol that acknowledges that PC 105 has the proper decryption
25 keys to decrypt protected multimedia content. The DRM protocol may be

1 predetermined between the PC 105 and the source (i.e., the website) prior to the
2 multimedia content being received.

3 DRM techniques allow a user of a PC authorized to record copyrighted
4 multimedia content to play back the multimedia content and prevent other
5 computers or other users of the PC from playing back the recorded multimedia
6 content, since only the authorized user on the PC has the proper decryption keys.

7 **Media Player**

8 Fig. 2 shows PC 105 which includes media player application 110 that is
9 configured to render and record multimedia content.

10 Media player 110 may use a filter graph 205 in order to render multimedia
11 content. Media player 110 creates filter graph 205 whenever new multimedia
12 content is received by media player 110. Filter graph 205 is destroyed once media
13 player 110 stops receiving multimedia content. This allows only a single instance
14 of multimedia to be played by the media player 110.

15 Filter graph 205 is comprised of multiple filters or components that are
16 linked with one another in order to process multimedia content. Such filters or
17 components may be implemented as software components. In certain cases, the
18 filters or components may simply pass on multimedia content without performing
19 any processing. Certain filters or components are needed to render multimedia
20 content, while other filters or components are optional.

21 It is contemplated that filter graph 205 is created and the multiple filters or
22 components that were previously installed in the computer are added to the filter
23 graph 205 when rendering either video or audio content. This may be referred to
24 as installation. As further discussed below, installation may include all or selected
25 filters or components.

1 A multimedia content separator 210 receives and separates (i.e., parses)
2 audio and video content streams from a source such as websites 125 of Fig. 1.
3 Multimedia content is typically compressed when transmitted from a source.
4 Compressed video content is received by a video decompressor component 215
5 and decompressed. Compressed audio content is received by audio decompressor
6 component 220 and decompressed.

7 Decompressed video and audio content are passed on to stream recorder
8 115 which includes a video recording engine 225 and an audio recording engine
9 230. Filter graph 205 provides for the ability to add and delete particular software
10 component (i.e., filter), and stream recorder 115 is such a software component. In
11 other words stream recorder 115 is an optional filter or component that may be
12 included in filter graph 205. If multimedia content is identified as protected by
13 DRM (i.e., the PC 105 is not authorized to record the multimedia content), stream
14 recorder 115 is not loaded or added to filter graph 205. Otherwise, if PC 105 is
15 authorized (i.e., has the proper DRM decryption keys to) to record the protected
16 multimedia content, stream recorder 115 is added to the filter graph 205. In
17 certain cases, video recording engine 225 and audio recording engine 230 are
18 treated as separate filters or components, and as such may be added or omitted in
19 filter graph 205.

20 Decompressed video content is received by video recording engine 225 and
21 decompressed audio content is received by audio recording engine 230. In certain
22 cases, as discussed below, video recording engine 225 records received video
23 content and audio recording engine 230 records received audio content. Video
24 and audio content may be time stamped at video recording engine 225 and audio
25 recording engine 230 in order to synchronize video and audio.

1 Regardless of whether recording is performed at video recording engine
2 225 and/or audio recording engine 230, video content is passed on to a video
3 digital signal processor (DSP) interface 235 and audio content is passed on to an
4 audio DSP interface 240. Video recording engine 225 and audio recording engine
5 230 may be considered as digital signal processors and are provided with
6 respective DSP interfaces 235 and 240.

7 Video DSP interface 235 sends video content to a video renderer 245 that
8 processes the video content for use by a video output device such as a display (not
9 shown) of PC 105. Audio DSP interface 240 sends audio content to an audio
10 renderer 250 that processes the audio content for use by audio output device such
11 as an audio driver card (not shown) of PC 105.

12 When audio recording engine 230 is instructed to record audio content,
13 audio content received by audio recording engine 230 is sent to an audio writer
14 component 255. Audio writer component 255 records the audio content to a local
15 storage device such as hard disk 260. Audio writer component 255 may compress
16 audio content in order to save storage space. Audio content may be recorded in
17 particular format such as Windows® Media Audio (WMA) format. Similarly,
18 when video recording engine 225 is instructed to record video content, video
19 content received by video recording engine 225 is sent to a video writer
20 component 265. Video content may be compressed by video writer component
21 265 and saved in a particular format such as Windows® Media Video (WMV)
22 format. Video writer component 265 records video content to hard disk 260. In
23 certain cases, audio recording engine 230 and video recording engine 225 may
24 send content to the same writer component where the writer component
25 multiplexes the audio and video content into a format such as audio video

1 interleave (AVI) and saves the multiplexed content as a single file in hard disk
2 260.

3 Stream Recorder

4 Fig. 3 shows operation of stream recorder 115 in PC 105. Stream recorder
5 115 includes a recording engine 305 which includes video recording engine 225
6 and audio recording engine 230.

7 Recording engine 305 may be implemented as a plug-in software
8 component, and in particular defined as a component object model (COM) object.
9 COM objects are defined by the Microsoft® Corporation, and are identified by
10 particular globally-unique identifiers (GUID). COM objects further provide
11 specific interfaces to access or communicate with other COM objects. Interfaces
12 provide a handshake protocol for format negotiation. For example, format
13 negotiation defines an input format which recording engine 305 receives and an
14 output format which recording engine 305 sends.

15 In this case, recording engine 305 has an interface 307 which may be
16 referred to as a "RecordingEngine" interface that may be called by other objects
17 such as user interface (UI) components which control recording behavior of
18 recording engine 305. "RecordingEngine" interface 307 supports operations such
19 as "Start Recording", "Pause Recording" and "Stop Recording". Furthermore.
20 recording engine 305 uses an interface 308(1) and 308(2) that may be referred to
21 as "RecordingEngineEvents" interface that is used to notify other objects or UI
22 components of changes in recording states of recording engine 305.

23 During its installation, the recording engine 305 registers itself with an
24 operating system of PC 105 as either an audio recording engine plug-in (e.g.,
25 audio recording engine 230) or a video recording engine plug-in (e.g., video

1 recording engine 225), and registers itself as a plug-in that may be used by media
2 player 110.

3 When registered and enabled, the recording engine 305 is loaded when
4 filter graph 205 is created to render audio (i.e., audio recording engine 230 is
5 loaded if the audio content is non-protected or is protected-with-recording-
6 permission) and/or video (i.e., video recording engine 225 is loaded if the video is
7 non-protected or protected-with-recording-permission).

8 A user may initiate data flow through recording engine 305 by indicating
9 any multimedia content to be played at media player 110. Media player 110
10 constructs (installs and links) the appropriate filters to create filter graph 205 to
11 process the media content as described in Fig. 2. If recording engine 305 is
12 enabled, multimedia player 110 detects whether recording engine 305 is able to
13 process the format of the multimedia content through format negotiation. If
14 format negotiation succeeds, the recording engine 305 is included in the filter
15 graph 205 of Fig. 2, allowing for recording of multimedia content. Media player
16 110 runs filter graph 205 which allows the multimedia content to be rendered (i.e.,
17 played).

18 A flag may be set in recording engine 305 to indicate whether content is to
19 be recorded. If the flag is set to true, a writer component such as audio writer 255
20 and video writer 265 has either been initialized, or is created and initialized.

21 The recording engine 305 may be implemented as a singleton COM object
22 which provides a maximum of one instance of the recording engine 305 for audio
23 or video (i.e., an audio and video recording engine may concurrently be present,
24 but only one audio and one video recording engine may be present at a time).

1 Since the recording engine 305 is a singleton COM object, when different
2 UI components reference a recording engine object, they are referenced to the
3 particular instance of recording engine 305.

4 Stream recorder 115 includes recording panel 310. Recording panel 310
5 provides a UI that allows a user to start, pause and stop recording, and may further
6 advise the user of current status of recording (e.g., currently recording, currently
7 paused, currently stopped). The recording panel 310 may be implemented as a
8 plug-in COM object that communicates with recording engine 305 through COM
9 defined interfaces, and in this example "RecordingEngine" interface 307 and
10 "RecordingEngineEvents" interface 308(1). Recording panel 310 provides for a
11 user to control settings that affect recording engine 305. Recording panel 310 is
12 created when the user invokes a UI for a particular setting or settings supported by
13 recording panel 310. Recording panel 310 is destroyed when the user closes the
14 particular UI area or chooses to view a different settings UI (i.e., UI for a different
15 functionality, such as a graphic equalizer).

16 When the recording panel 310 is created, it creates or looks for an instance
17 of recording engine 305 and receives a pointer to "RecordingEngine" interface
18 307. The recording panel 310 checks whether the recording engine 305 is
19 correctly installed and thereby enabled by media player 110, and if not an error
20 message is displayed. If the recording engine 305 is correctly installed and
21 enabled, recording panel 310 can subscribe to the events of recording engine 305
22 via "RecordingEngineEvents" interface 308(1) and as a result it is notified of any
23 change of events from recording engine 305. A query through "RecordingEngine"
24 interface 307 may also be performed to recording engine 305 to determine the
25 current recording status. The recording engine 305 is aware of the current

1 recording status. Likewise recording panel 310 may receive from media player
2 110 the current playback status and subscribe to receive from media player 110
3 notifications such as playback status changes. The recording panel 310 may
4 update its UI depending upon the current recording and playback status that is
5 received. For example, if the media player is stopped and is not playing any
6 media content, the UI to “start recording” is disabled.

7 Commands initiated at the recording panel 310 results in appropriate
8 changes to other controls on recording panel 310. For example, if the “start
9 recording” command is initiated at recording panel 310, the recording panel 310
10 sets a name of a to-be-encoded multimedia file, retrieves metadata of the current
11 multimedia content from media player 110 and initiates the recording engine 305
12 to start recording.

13 When a recording event occurs (e.g., recording is completed), a
14 corresponding event handler of the recording panel 310 is called by the recording
15 engine 305 through the “RecordingEngineEvents” interface 308(1). Upon
16 receiving a recording event, the recording panel 310 updates its UI. For example,
17 when recording has completed, the “stop recording” UI may be disabled and the
18 “start recording” UI may be enabled.

19 Stream recorder 115 includes a recording coordinator 315 that is
20 implemented as a background UI plug-in of media player 110. Furthermore,
21 recording coordinator 315 may be implemented as a COM object that interfaces
22 with recording engine 305.

23 An instance of recording coordinator 315 may be created when media
24 player 110 is started. The particular instance is deleted when media player 110
25 stops playing content. The recording coordinator 315 provides the ability for

1 applications external to media player 110 to control recording behavior of
2 recording engine 305. In this example, an application tool-bar recording panel 320
3 is shown which may be part of PC 105's operating system.

4 The recording coordinator 315 may have a hidden window associated with
5 it which is created at startup of media player and is destroyed when the media
6 player 110 is shut down. The hidden window provides a messaging mechanism
7 for the recording coordinator 315 and an external application such as tool-bar
8 recording panel 320 to communicate recording information back and forth.

9 Recording panel 315 is able to receive playback change notifications from
10 media player 110 and sends the notifications to an external application such as
11 tool-bar recording panel 320. Further, recording state change notifications
12 received from recording engine 305 through "RecordingEngineEvents" interface
13 308(1) may be received and sent to external applications such as tool-bar
14 recording panel 320.

15 When recording coordinator 315 is created, it creates or looks for an
16 instance of recording engine 305 and receives a pointer to "RecordingEngine"
17 interface 307. Through "RecordingEngineEvents" interface 308(2), recording
18 coordinator 315 subscribes to the recording events of recording engine 305 and
19 further subscribes to playback state notifications from media player 110.
20 Recording coordinator 315 checks whether an external application such as tool-bar
21 recording panel 320 exists. If the external application is recognized, recording
22 coordinator 315 sends a message to the external application that indicates
23 playback and current recording states.

24 The recording coordinator 315 may also listen to predefined messages from
25 external applications (e.g., tool-bar recording panel 320) indicating recording

1 start/stop/pause behavior. When a specific message containing a recording
2 command from an external application, in this example tool-bar recording panel
3 320, is received, the recording coordinator 315 passes that command to the
4 recording engine 305 via the "RecordingEngine" interface 307.

5 When a recording event occurs, such as when recording is completed, or
6 recording is paused, or recording is stopped, the recording coordinator 315 sends a
7 corresponding message to the tool-bar recording panel 320 so that tool-bar
8 recording panel 320 may update its UI state.

9 Likewise, when playback state changes in media player 110 the recording
10 coordinator 315 receives the corresponding notification from media player 110.
11 Recording coordinator 315 sends the notification to tool-bar recording panel 320
12 so that tool-bar recording panel 320 may update its UI state.

13 The tool-bar recording panel 320 provides an accessible UI component
14 through which a user can control recording functionality. A user may not have
15 media player 110 as a foreground application at all times when media is being
16 played. For example, the media player 110 application window may be minimized
17 or put in the background. Tool-bar recording panel 320 may be optionally turned
18 on by a user. Particular scenarios include placing a window on a taskbar next to a
19 system clock, providing start, pause, stop recording controls to access recording
20 functionality. Similar to the recording panel 310, the tool-bar recording panel 320
21 provides a UI to start, pause and stop recording. The difference is that the
22 recording panel 320 is a component of media player 110, while the tool-bar
23 recording panel 320 is an external application. In the specific example where the
24 tool-bar recording panel 320 appears as a window on the taskbar next to the
25

1 system clock, it is a desk band object (i.e., a plug-in component to the operating
2 system shell).

3 The two UI components to recording engine 305 allow users to control
4 recording either through media player 110 through recording panel 310 or through
5 an operating system desktop through tool-bar recording panel 320.

6 **Exemplary Recording Session**

7 Fig. 4 shows a process 400 describing control flow in an example recording
8 session.

9 At block 405, the media player 110 is started. A user may initiate media
10 player 110 to start rendering or playing multimedia content.

11 At block 410, upon media player 110 starting up, media player 110 creates
12 the recording coordinator 315. When recording coordinator 315 is created, it
13 creates an instance of the recording engine 305. Recording coordinator 315
14 subscribes to recording events of the recording engine 305 through the
15 “RecordingEngineEvents” interface 308(1) and obtains current playback state
16 from media player 110 and the current recording state from the recording engine
17 305 using the “RecordingEngine” interface 307. Recording coordinator 315 looks
18 for an external application such as tool-bar recording panel 320. If the tool-bar
19 recording panel 320 is found, recording coordinator 315 sends a current recording
20 and playback status message to tool-bar recording panel 320.

21 At block 415, the tool-bar recording panel 320 is enabled. Tool-bar
22 recording panel 320 may be enabled by a user through a desktop interface such as
23 a taskbar menu option. When tool-bar recording panel 320 is created it checks
24 whether media player 110 is active and running. If media player 110 is active and
25 running, tool-bar recording panel 320 detects if recording coordinator 315 exists as

1 part of media player 110 (i.e., a child window within an application window of
2 media player 110). If the recording coordinator 315 is found, the tool-bar
3 recording panel 320 sends a message that it was enabled by a user to the recording
4 coordinator 315. The message may be sent by passing a unique window handle
5 associated with the tool-bar recording panel 320. The recording coordinator 315
6 in turn sends the tool-bar recording panel 315 a message indicating current
7 recording and playback status. The tool-bar recording panel 315 updates its UI per
8 the current recording and playback status. All the recording controls are disabled
9 at this stage.

10 At block 420, the recording panel 310 may be activated by a user through
11 the media player 110. In particular the media player 110 creates an instance of the
12 recording panel 310. When started, the recording panel 310 creates an instance of
13 the recording engine 305; however if recording engine 305 has been created at
14 step 410, only a single instance of recording engine 305 may be present. Through
15 the "RecordingEngine" interface 307 recording panel 310 references the existing
16 instance of recording engine 305 allowing queries to be performed as to the
17 current state of the recording engine 305. Through "RecordingEngineEvents"
18 interface 308(2) recording panel 310 subscribes to events of recording engine 305.
19 Recording panel 310 also receives playback state change notifications of the
20 media player 110 which allows queries as to current playback state of the media
21 player 110.

22 At block 425, media player 110 is instructed to play multimedia content,
23 such as multimedia content received from an Internet radio station. Media player
24 110 builds an instance of a filter graph such as filter graph 205.

1 During installation, the recording engine 305 registers itself to an
2 addressable location in a hard drive of PC 105 (for example, in the system
3 registry) as either an audio recording engine plug-in (e.g., audio recording engine
4 230) or a video recording engine plug-in (e.g., video recording engine 225). When
5 rendering of audio or video content is performed, media player 110 detects the
6 recording engine 305 as a registered plug-in (filter) for the filter graph. Media
7 player 110 may try to create an instance of the recording engine 305; however
8 since an instance has been created, media player 110 references the existing
9 instance of recording engine 305 and adds it to the filter graph. Format
10 negotiation is performed by media player 110 with recording engine 305 as to the
11 format of uncompressed content that is input to the recording engine 305 and the
12 format of uncompressed content to be output from the recording engine 305.
13 Content is played using the created filter graph. The media player 110 may send
14 event notifications to subscriber components indicating the change of state from
15 “not playing” to “playing”. Recording panel 310 receives the event notification
16 and updates its recording UI to enable recording. The recording coordinator 315
17 receives the event notification and sends a corresponding message to tool-bar
18 recording panel 320 to update its UI to enable recording.

19 At block 430, a user may initiate recording through the recording panel
20 310. (The user may initiate recording either through the recording panel 310 or
21 through tool-bar recording panel 320; however in this example, the recording is
22 initiated through recording panel 310). The recording panel 310 initializes the
23 recording engine 305 through “RecordingEngine” interface 307 with a name of the
24 file to record the content to. As an optional, the name of the file to record the
25 content to may be auto-generated using some user options such as the folder to

1 save the recorded file into and the date and time of recording. Recording panel
2 310 may query the media player 110 as to information which may be part of
3 metadata about the content that is being played. Information may include title,
4 author, and type of content. Recording panel 310 provides this information to the
5 recording engine 305 to save along with the recorded content. Recording panel
6 310 initiates recording engine 305 through the "RecordingEngine" interface 307.
7 The recording engine 305 changes its internal flag to "record" to indicate
8 recording. The next time uncompressed content passes through the created filter
9 graph, the recording engine 305 initializes recording by creating an instance of a
10 writer component such as audio writer 255 and video writer 265. The recording
11 engine 305 further sets up the appropriate input format for uncompressed content
12 received at the writer component, and output format for the compressed file that is
13 output by the writer component, and the output filename of the file recorded to a
14 storage device such as hard disk 260 of Fig. 2.

15 The recording engine 305 sends notification events to subscribers through
16 the "RecordingEngineEvents" interface 308(1) and 308(2) indicating start of
17 recording. The "recording panel" 310 receives the event notification and updates
18 its UI to indicate recording, disabling "Start Recording", and enabling "Pause
19 Recording" and "Stop Recording". Similarly the recording coordinator 315
20 receives the event notification and sends the event notification to the tool-bar
21 recording panel 320. The tool-bar recording panel 320 updates its UI by disabling
22 "Start Recording" and enabling "Stop Recording" and "Pause Recording". As
23 long as the internal flag of recording engine 305 is set to record, content samples
24 received by recording engine 305 are passed to the writer component to be
25 recorded before being passed along the filter graph for rendering.

1 At block 435, a user may stop recording by initiating a “stop recording”
2 command”. This action may be performed from the tool-bar recording panel 320
3 or through the recording panel 310. This example assumes that the action is
4 performed through the tool-bar recording panel 320. The tool-bar recording panel
5 320 receives the “stop recording” command from user and sends a message to
6 recording coordinator 315 to stop recording. The recording coordinator 315
7 indicates to recording engine 305 through “RecordingEngine” interface 307 to
8 stop recording. When recording engine 305 receives the indication from recording
9 coordinator 315, the recording engine 305 changes its internal flag to indicate that
10 no further recording is to take place and that content no longer is passed to the
11 writer component for recording.

12 The recording engine 305 finalizes recording of the recorded file processed
13 by the writer component. Recording engine 305 may add the metadata that was
14 queried by the media player 110 in block 430 to the recorded file. Recording
15 engine 305 closes the file to be recorded, and deletes the writer component.

16 The recording engine 305 sends an event notification to subscribers through
17 the “RecordingEngineEvents” interface 308(1) and 308(2) indicating end of
18 recording. The “recording panel” 310 receives the event notification and updates
19 its UI to indicate end of recording by enabling “Start Recording” and disabling
20 “Stop Recording” and “Pause Recording”. Similarly the recording coordinator
21 315 receives the event notification and passes it on to the tool-bar recording panel
22 320. The recording engine 305 may add the recorded file to a folder or library in
23 PC 105.
24
25

Exemplary Computer Environment

The subject matter is described in the general context of computer-executable instructions, such as program components, being executed by a computer such personal computer 105 of Fig. 1. Generally, program components include routines, programs, objects, components, data structures, etc. that perform particular tasks or implement particular abstract data types. Moreover, those skilled in the art will appreciate that the subject matter may be practiced with other computer system configurations, including hand-held devices, multiprocessor systems, microprocessor-based or programmable consumer electronics, network PCs, minicomputers, mainframe computers, and the like. In a distributed computer environment, program components may be located in both local and remote memory storage devices.

Fig. 5 shows a general example of a computer 530 that is used in accordance with the subject matter. Computer 530 is shown as an example of a computer that can perform the functions of a server computer or a remote client computer. Computer 530 includes one or more processors or processing units 532, a system memory 534, and a bus 536 that couples various system components including the system memory 534 to processors 532. Processors 532 may initiate or configured to initiate a session with another computer.

The bus 536 represents one or more of any of several types of bus structures, including a memory bus or memory controller, a peripheral bus, an accelerated graphics port, and a processor or local bus using any of a variety of bus architectures. The system memory includes read only memory (ROM) 538 and random access memory (RAM) 540.

1 A basic input/output system (BIOS) 542, containing the basic routines that
2 help to transfer information between elements within computer 530, such as
3 during start-up, is stored in ROM 538. Computer 530 further includes a hard disk
4 drive 544 for reading from and writing to a hard disk, not shown, a magnetic disk
5 drive 546 for reading from and writing to a removable magnetic disk 548, and an
6 optical disk drive 550 for reading from or writing to a removable optical disk 552
7 such as a CD ROM or other optical media. The hard disk drive 544, magnetic disk
8 drive 546, and optical disk drive 550 are connected to the bus 536 by an SCSI
9 interface 554 or some other appropriate interface. The drives and their associated
10 computer-readable media provide nonvolatile storage of computer readable
11 instructions, data structures, program components and other data for computer
12 530.

13 Although the exemplary environment described herein employs a hard disk,
14 a removable magnetic disk 548 and a removable optical disk 552, it should be
15 appreciated by those skilled in the art that other types of computer readable media
16 which can store data that is accessible by a computer, such as magnetic cassettes,
17 flash memory cards, digital video disks, random access memories (RAMs) read
18 only memories (ROM), and the like, may also be used in the exemplary operating
19 environment.

20 A number of program components may be stored on the hard disk,
21 magnetic disk 548, optical disk 552, ROM 538, or RAM 540, including an
22 operating system 558, one or more application programs 560, other program
23 components 562, and program data 564.

24 A user may enter commands and information into computer 530 through
25 input devices such as keyboard 566 and pointing device 568. Other input devices

1 (not shown) may include a microphone, joystick, game pad, satellite dish, scanner,
2 or the like. These and other input devices are connected to the processing unit 532
3 through interface 570 that is coupled to bus 536. Monitor 572 or other type of
4 display device is also connected to bus 536 via an interface, such as video adapter
5 574.

6 Computer 530 operates in a networked environment using logical
7 connections to one or more remote computers, such as a remote computer 576.
8 The remote computer 576 may be another personal computer, a server, a router, a
9 network PC, a peer device or other common network node, and typically includes
10 many or all of the elements described above relative to computer 530, although
11 only a memory storage device 578 has been illustrated in Fig. 5. The logical
12 connections depicted in Fig. 5 include a local area network (LAN) 580 and a wide
13 area network (WAN) 582. Such networking environments are commonplace in
14 offices, enterprise-wide computer networks, intranets, and the Internet.

15 When used in a LAN networking environment, computer 530 is connected
16 to the local network 580 through a network interface or adapter 584. When used
17 in a WAN networking environment, computer 530 typically includes a modem 586
18 or other means for establishing communications over the wide area network 582,
19 such as the Internet. The modem 586, which may be internal or external, is
20 connected to the bus 536 via a serial port interface 556. In a networked
21 environment, program components depicted relative to the personal computer 530,
22 or portions thereof, may be stored in the remote memory storage device. It will be
23 appreciated that the network connections shown are exemplary and other means of
24 establishing a communications link between the computers may be used.

1 Generally, the data processors of computer 530 are programmed by means
2 of instructions stored at different times in the various computer-readable storage
3 media of the computer. Programs and operating systems are typically distributed,
4 for example, on floppy disks or CD-ROMs. From there, they are installed or
5 loaded into the secondary memory of a computer. At execution, they are loaded at
6 least partially into the computer's primary electronic memory.

7 The subject matter described herein includes these and other various types
8 of computer-readable storage media when such media contain instructions or
9 programs for implementing the steps described below in reference to Fig. 5 in
10 conjunction with a microprocessor or other data processor.

11 The subject matter also includes the computer itself when programmed
12 according to the methods and techniques described below. Furthermore, certain
13 sub-components of the computer may be programmed to perform the functions
14 and steps described below. The subject matter includes such sub-components
15 when they are programmed as described. In addition, the subject matter described
16 herein includes data structures, described below, as embodied on various types of
17 memory media.

18 For purposes of illustration, data, programs and other executable program
19 components, such as the operating system are illustrated herein as discrete blocks,
20 although it is recognized that such programs and components reside at various
21 times in different storage components of the computer, and are executed by the
22 data processor(s) of the computer.

23 Although the invention has been described in language specific to structural
24 features and/or methodological acts, it is to be understood that the invention
25 defined in the appended claims is not necessarily limited to the specific features or

1 acts described. Rather, the specific features and acts are disclosed as exemplary
2 forms of implementing the claimed invention.
3
4
5
6
7
8
9
10
11
12
13
14
15
16
17
18
19
20
21
22
23
24
25